

# Waterproof Stand-Alone Access Controller Keypad

Model Number:JS-S100C



## Key Specifications/Special Features

---

Product name: waterproof stand-alone access controller

Model no: JS-S100C

Parameter:

Dimensions: 120Lx80Wx25D (mm)

Working voltage: DC 9V-28V

Operating temperature: -45°C-60°C

Operating humidity: 10%-90%

Electric lock output:  $\leq 3\text{a}$

Alarm output:  $\leq 20\text{A}$

Output short-circuits protection time: open door time: 0~99 seconds (adjustable)

Weight: 0.6kg

Box size: 23\*15\*7cm

Standard packaging: 21cps

Cartons size: 58\*48\*25cm

Standard packaging: 22pcs

Features:

Waterproof degree: IP68

With anti-theft alarm output for external alarm device

With built-in anti-theft equipment

Support enrolling cards continuously

Perfect design with back-light and fashion silver finishing

Waterproof design for outdoor using in the rain

Strong standalone function device can be used as WG26 reader alone

Capacity: 2000 user's cards, 2000 codes

Access ways: cards, code, card+code

Low power: static current less than 30mA

Support only keypad

Users can reset private passwords

Search fast less than 0.1S

Wiegand output W26 for card and W4 for codes

Using keypad to delete lost cards for safety

Short circuit protect: when relay or alarm output short circuit, it will shut up output in 100 $\mu$  S